

**EXTENDED RANGE OF STANDARD "ONE FOR ALL"
PHOTOELECTRIC TUBULAR M18 SENSORS**


- All optic functions
- Improved EMI immunity
- Improved ambient light immunity
- Improved laser safety level
- M18 flat plastic with universal mounting
- Short plastic housing models
- Available in M18 metal housing
- Stainless steel housing models
- Axial or radial optics, cable or connector
- Standard 4-wire NO-NC NPN or PNP output
- M12 pigtail models available
- IO-Link connectivity V1.1 with double channel

Detection properties

Nominal sensing distance	400 mm
Sensitivity adjustment	Trimmer

Application

Description	Tubular M18 - axial optic
Functions	Diffuse beam

Outputs

Output type	PNP NO-NC
Response time	0,500

Electrical data

Operating Voltage	10-30 VDC
Emission	LED IR

Mechanical data

Dimensions	Ø18x67
Connections	2 m cable
Material	Plastic - PBT / PMMA

Generical Data

Dimensions	Ø18x67
------------	--------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail info@datasensing.com

date of printing

27/04/2022 07:24:51