



COMPACT SIZE AND HIGH PERFORMANCE FOR THE MOST CHALLENGING DETECTION APPLICATIONS LINKED TO YOUR INDUSTRY 4.0 APPLICATIONS

- Compact dimensions (14x42x25 mm)
- Background suppression for transparent and shiny objects
- Contrast sensors up to 25 kHz switching frequency
- Extremely focused spot, under 1 mm (LASER model)
- Very high resolution LASER models
- INOX AISI 316L model
- Extended IO-Link parametrization with counter
- All output fully PNP/NPN/PP IO-Link configurable
- IO-link COM2
- IO-Link dual channel with no jitter addition

Detection properties

Nominal sensing distance 2 m

Sensitivity adjustment Teach-in

Application

Description Compact slim case

Functions Polarized retroreflective for clear object

Outputs

Output type PNP - Dark/Light sel.

Response time 0,250

Electrical data

Operating Voltage 10-30 VDC

Emission LED Red

Mechanical data

Dimensions 14x43x25

Connections M8

Material Plastic - ABS / PMMA

Generical Data

Dimensions 14x43x25

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail info@datasensing.com

date of printing

20/09/2022 11:50:24