



## COMPLETE LINE OF AMPLIFIED SUBMINIATURE PHOTOELECTRIC SENSORS

- 15 mm, 20 mm, 30 mm and 50 mm fixed focus proximity
- 1,5 m retroreflective and 1 m polarized retroreflective
- 2 m through beam models
- Amplified NPN or PNP output with NO-NC output

### Detection properties

Nominal sensing distance	20mm
Sensitivity adjustment	n/a

### Application

Function Principle	Fix focus beam
Description	Subminiature slim case
Optic position	Radial 90°
Functions	Fix focus beam

### Outputs

Output type	PNP Lon
Output Function	Lon
Switching frequency	590Hz
Response time	1ms

### Electrical data

Operating Voltage	10...30VDC
No-Load supply current	≤ 20mA
Load current	≤50mA
Output voltage drop	≤1,45V@Iload=50mA
LED indicators	Yellow (output status)
Short-circuit protection	YES

Reverse Polarity Protection	Yes
Emission	LED Red (640nm)
Interference to external light	according to EN 60947-5-2 : 2020
Impulsive Overvoltage Protection	Yes
Insulation resistance	>20 M $\Omega$ 500 Vdc, between electronics and housing
Contact resistance	500 Vac 1 min., between electronics and housing

### Mechanical data

Dimensions	8x26x12
Housing Material	Plastic ABS / PMMA
Connections	2m cable
Active Head Material	PMMA
Storage temperature	- 35°C...+75°C
Material	
Diameter/Dimension	Cubic

### Test/Approvals

Approvals	CE cULus
Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)

### Generical Data

Dimensions	8x26x12
Operating Temperature	- 20°C...+ 55°C
Mechanical Protection	IP67

## Datasensing S.r.l.

Strada S.Caterina, 235

41122 Modena (MO)

Tel. 059 420411

Fax 059 253973

E-mail [info@datasensing.com](mailto:info@datasensing.com)

### date of printing

19/05/2023 13:33:19