



THE UNIVERSAL MINIATURE PHOTOELECTRIC SENSORS

- Two threaded front mounting holes
- Two slotted rear mounting holes
- Anti-tampering sensor (no adjustment)
- High speed high resolution RGB contrast sensor available
- Transparent object detection
- M8 connector and cable models
- PNP or NPN models with Light/Dark selection by wire
- Plastic housing, IP67 mechanical protection
- IO-Link COM2 communication protocol
- IO-Link V1.1.2 version
- IO-Link extended parametrization for monitoring and maintenance

Detection properties

Nominal sensing distance	100 mm
Sensitivity adjustment	Ext. Teach

Application

Description	Miniature universal multi-holes
Functions	Background suppression

Outputs

Output type	PNP – Dark/Light sel.
Response time	1,000

Electrical data

Operating Voltage	10-30 VDC
Emission	LED Red

Mechanical data

Dimensions	12x32x20
Connections	2 m cable
Material	Plastic ABS/PMMA/PC

Generical Data

Dimensions	12x32x20
------------	----------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail info@datasensing.com

date of printing

15/02/2022 07:06:32