

## COMPACT SIZE AND HIGH PERFORMANCE FOR THE MOST CHALLENGING DETECTION APPLICATIONS LINKED TO YOUR INDUSTRY 4.0 APPLICATIONS



- Compact dimensions (14x42x25 mm)
- Background suppression for transparent and shiny objects
- Contrast sensors up to 25 kHz switching frequency
- Extremely focused spot, under 1 mm (LASER model)
- Very high resolution LASER models
- INOX AISI 316L model
- Extended IO-Link parametrization with counter
- All output fully PNP/NPN/PP IO-Link configurable
- IO-link COM2
- IO-Link dual channel with no jitter addition

### Detection properties

Nominal sensing distance

12m

Sensitivity adjustment

Trimmer

### Application

Function Principle

Polarized retroreflective

Description

Compact slim case

Optic position

Radial 90°

Functions

Polarized retroreflective

### Outputs

Output type

PNP L/D selectable

Output Function

L/D selectable

Response time

0,5

### Electrical data

Operating Voltage

12...30VDC

No-Load supply current

≤ 30mA

Output voltage drop

≤2V@Iload=100mA

LED indicators

Yellow (status output) or (output/alarm) Green (powerON)

Short-circuit protection	YES
Reverse Polarity Protection	Yes
Emission	LASER Red
Interference to external light	according to EN 60947-5-2 : 2020
Impulsive Overvoltage Protection	Yes
Insulation resistance	>20 M $\Omega$ 500 Vdc, between electronics and housing
Contact resistance	500 Vac 1 min., between electronics and housing

### Mechanical data

Dimensions	14x43x25
Housing Material	ABS(Housing), PMMA (Optics)
Connections	150mm PVC cable + M12 plug
Active Head Material	PMMA
Storage temperature	- 25°C...+70°C
Material	Plastic - ABS / PMMA
Diameter/Dimension	Cubic

### Test/Approvals

Approvals	CE cULus
Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)

### Generical Data

Dimensions	14x43x25
Operating Temperature	- 25°C...+ 55°C (Without freeze)
Mechanical Protection	IP67

## Datasensing S.r.l.

Strada S.Caterina, 235

41122 Modena (MO)

Tel. 059 420411

Fax 059 253973

E-mail [info@datasensing.com](mailto:info@datasensing.com)

### date of printing

07/06/2023 12:34:43