

ALL REGISTRATION MARK DETECTION APPLICATIONS



- Teach-in, Remote settings
- Red/green or white LED emission
- Various interchangeable lenses and fiber-optic models
- Metal housing with orientable optics and connector

Detection properties

| | |
|--------------------------|----------|
| Nominal sensing distance | 9mm |
| Spot dimension | Ø 3 mm |
| Sensitivity adjustment | Teach-in |

Application

| | |
|--------------------|-------------------------------|
| Function Principle | Contrast mark detection |
| Description | Standard case - circular spot |
| Optic position | axial |
| Functions | Contrast mark detection |

Outputs

| | |
|-----------------|--------------------|
| Output type | PNP L/D selectable |
| Output Function | L/D selectable |
| Response time | 0,025 (20 kHz) |

Electrical data

| | |
|-------------------|------------|
| Operating Voltage | 10...30VDC |
|-------------------|------------|

| | |
|----------------------------------|-------------------------------------------------|
| No-Load supply current | ≤ 80mA |
| Output voltage drop | ≤2V |
| LED indicators | red OUTPUT greenREADY |
| Short-circuit protection | YES |
| Reverse Polarity Protection | Yes |
| Emission | LED White |
| Interference to external light | according to EN 60947-5-2 : 2020 |
| Impulsive Overvoltage Protection | Yes |
| Insulation resistance | >20 MΩ 500 Vdc, between electronics and housing |
| Contact resistance | 500 Vac 1 min., between electronics and housing |

Mechanical data

| | |
|----------------------|----------------|
| Dimensions | 31x58x82 |
| Housing Material | Metal - Zamak |
| Connections | M12 plug |
| Active Head Material | Glass |
| Storage temperature | - 20°C...+70°C |
| Material | |
| Diameter/Dimension | Cubic |

Test/Approvals

| | |
|-----------------------|------------------------------------------------------------------------|
| Approvals | CE cULus |
| Shocks and vibrations | 0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6) |

Generical Data

| | |
|-----------------------|----------------|
| Dimensions | 31x58x82 |
| Operating Temperature | -10°C ... 55°C |
| Mechanical Protection | IP67 |

Datasensing S.r.l.

Strada S.Caterina, 235

41122 Modena (MO)

Tel. 059 420411

Fax 059 253973

E-mail info@datasensing.com

date of printing

21/11/2023 12:40:19