

# Basic

## NON-CONTACT DETECTION COST EFFECTIVE AND RELIABLE DETECTION OF ANY METAL PART



- Standard proximity M4, M5, M8, M12, M18, M30
- Double range (i.e. M12 4mm, M18 14mm, M30 20mm)
- Unshielded or shielded models for flush mounting
- Nickel brass or stainless steel short and long housing
- Ecolab and Diversey certifications for industrial detergents
- Multi-voltage, Metal face, Weld field immune models
- NO/NC, NPN or PNP output and programmable versions.

### Detection properties

Nominal sensing distance	4mm
Operating distance	0...3,24mm
Standard target	12x12mm FE360
Correction Factor	copper: 0,4...0,5 / aluminium: 0,4...0,6 / brass: 0,5...0,7 / stainless steel: 0,7...1,05
Repeat Accuracy	< 3% (UB 24V Ta=23°C ±5°C)
Hysteresis	< 10%

### Application

Description	M12 short case no-flush mount
Functions	Proximity

### Outputs

Output type	PNP
Output Function	NO

Switching frequency	1kHz
Response time	0,5

### Electrical data

Operating Voltage	10...30Vdc
No-Load supply current	≤ 10mA
Load current	200mA
Output voltage drop	≤ 1,8V @100mA
Max ripple content	≤ 10%
LED indicators	Yellow LED output state
Time delay before availability	≤ 50ms
Short-circuit protection	Yes
Reverse Polarity Protection	Yes
Emission	≥100kHz
Protection against inductive loads	Yes

### Mechanical data

Mounting	Unshielded
Dimensions	Ø12x54
Housing Material	Nickel-plated brass
Connections	M12 Plug
Active Head Material	LCP
Tightening torque	6Nm
Material	Nickel-plated brass
Diameter/Dimension	M12

### Test/Approvals

Approvals	CE cULus ECOLAB DIVERSEY
-----------	--------------------------

### Accessories

Supplied Accessories	2 nuts M12x1
----------------------	--------------

### Generical Data

Dimensions	Ø12 / L = 54mm
Operating Temperature	-25°C...+60°C
Mechanical Protection	IP67

---

---

**Datasensing S.r.l.**

Strada S.Caterina, 235

41122 Modena (MO)

Tel. 059 420411

Fax 059 253973

E-mail [info@datasensing.com](mailto:info@datasensing.com)

**date of printing**

21/12/2023 11:50:04