

## ADVANCED GLOBAL STYLE MINIATURE PHOTOELECTRIC SENSOR



- 50-250 mm background suppression
- 0.7 m proximity, 150 mm with narrow beam
- 4 m polarized retroreflective
- 15 m through beam
- Light and dark trimmer models
- Standard 3-wire output configuration

### Detection properties

Nominal sensing distance	15m
Sensitivity adjustment	Trimmer

### Application

Function Principle	Through beam emitter and receiver
Description	Miniature global standard front holes
Optic position	Radial 90°
Functions	Through beam emitter and receiver

### Outputs

Output type	PNP Don
Output Function	Don
Switching frequency	500Hz
Response time	1

### Electrical data

Operating Voltage	10...30VDC
-------------------	------------

No-Load supply current	≤ 30mA
Load current	≤100mA
Output voltage drop	≤2V@Iload=100mA
Short-circuit protection	YES
Reverse Polarity Protection	Yes
Emission	LED Infrared (870 nm)
Interference to external light	according to EN 60947-5-2 : 2020
Impulsive Overvoltage Protection	Yes
Insulation resistance	>20 MΩ 500 Vdc, between electronics and housing
Contact resistance	500 Vac 1 min., between electronics and housing

### Mechanical data

Dimensions	11x32x20
Housing Material	Plastic PBT / PMMA
Connections	M8 plug 4pin
Active Head Material	PMMA
Storage temperature	- 40°C...+70°C
Material	
Diameter/Dimension	Cubic

### Test/Approvals

Approvals	CE cULus
EMC compatibility	EN 60947-5-2
Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)

### Generical Data

Dimensions	11x32x20
Operating Temperature	- 25°C...+ 55°C
Mechanical Protection	IP67

## Datasensing S.r.l.

Strada S.Caterina, 235

41122 Modena (MO)

Tel. 059 420411

Fax 059 253973

E-mail [info@datasensing.com](mailto:info@datasensing.com)

**date of printing**

06/03/2024 08:48:15